AVerTouch P2P Setup

Copyright © AVer Information Inc. All rights reserved.





Mac P2P Setting SOP

- 1. Mac OSX P2P Setup Flow
- 2. How to Uninstall Mac Wi-Fi dongle driver Flow





1. Mac P2P Setup Flow

1. Download AVerTouch application from bleow URL.

www.averusa.com/education/support/avertouch

- 2. Unzip the file and install Wi-Fi dongle drive and AVerTouch on your MacBook
- 3. MacBook connects to M15W/M70W Wi-Fi (password is Averadmin).
- 4. Open Network Preference to select "Set Service Order..."
- 5. Open AVerTouch and connect to camera





1-1 Install Wi-Fi dongle drive



Note: File name may be different but the driver is a .pkg file



1-1-1 Install Wi-Fi dongle drive







1-2 MacBook connects to M15W/M70W Wi-Fi.





1-2-1 MacBook connects to M15W/M70W Wi-Fi. Enter Password:"AVeradmin"

This network requires a WF	"AVerM15W-5CF370575250" A2-PSK AES password.
Password:	AVeradmin
	✓ Show password
Show Networks	Cancel

AVer



1-2-2 Open Network Preference.

	in the cooking for rectrontist.	in In Presentation
	Turn Wi-Fi Off	💄 + Share \land
Convert to SmartArt	 AVI-Staff 12345678 Pic ARRIS-E36A ARRIS-E36A-5G AVerM15W-5CF37054300A AVerM15W-5CF3705974EA AVerM15W-5CF3705974EA AVerM15W-5CF370597550 AVerR01_BF9017F9 AVI-Guest AVI-Guest AVI-Guest-2.4G AVI-Staff-2.4G DIRECT-M15W-5CF370575250 DIRECT-NC1561000343-2msJv DIRECT-RSA1561000308-33ms dlink-868_2.4G dlink-868_5G heng AP Linksyscisco Linksysc	• tline •
	loin Other Network	
	JOIN OTHER NELWORK	



1-2-3 Select "Set Service Order..."

	Network		2 Search
Locati	on: Automatic	0	
 Wi-Fi Connected 802.11ac NIC 3 Connected Bluetooth PAN Not Connected USB-Sentroller Not Configured USB-SeastEther Not Connected B02.11ac NIC Not Connected 802.11ac NIC 2 Not Connected 802.11ac NIC 2 Not Connected Not Connected Not Connected Not Connected Not Connected ThundeIt Bridge Not Connected 	Status: Network Name: 802.1X:	Connected Wi-Fi is connected to AVI-Sta address 10.100.200.32. AVI-Staff Automatically join this Ask to join new networks Known networks will be join no known networks will be join no known networks are avail to manually select a networ Default Authenticated via EAP-PEAP Connect Time: 00:04:23	Turn Wi-Fi Off aff and has the IP aff and has the IP c network rks rks red automatically. If lable, you will have k. Disconnect (MSCHAPv2)
+ - * Duplicate Service Rename Service	✓ Show Wi-Fi status i	n menu bar	Advanced ?
Set Service Order			
Import Configuratio	ns		

9



1-2-4 Drag "Wi-Fi" to top of list and click "OK"





1-2-5 Click "Apply"

	Network	Q Search
Locat	ion: Automatic	•
Wi-Fi Connected	Status: Cor Wi-F	Fi is connected to AVI-Staff and has the IP
Bluetooth PAN	addr	ress 10.100.200.32.
Not Connected USB-Sentroller	✓ /	Automatically join this network
DM962astEther	Ask to join new networks Known networks will be joined au no known networks are available, to manually select a network.	Ask to join new networks Known networks will be joined automatically. If no known networks are available, you will have o manually select a network.
Not Connected 802.11ac NIC 2	802.1X: Def	ault Disconnect
Not Connected	Con	nect Time: 00:15:18
- * -	✓ Show Wi-Fi status in m	Advanced ?
		Revert





1-3 Open AVerTouch and choose doc cam







1-4 P2P Connection Complete







AVer





2-1 Open Uninstall.pkg

	RTLWIanU_Mac	OS10.9_MacOS10.14	_Driver_1830.20	.b36_1827.4.b36_UI_5.0.8.b9	
$\langle \rangle$: : · · ·		Q Search	
Favorites (AirDrop Recents	V	Table 1		- strest - stre	
Applications Desktop Documents Downloads	Install.pkg	Release_RTWlanU _MacOSX.txt	Uninstall.pkg	Utility_Release.txt	
iCloud					
Locations					
10_15 - Data 10 13					
Remote Disc					

Note: File name may be different but the driver is a .pkg file



2-2 Press Continue

	Welcome to the Wireless USB Adapter Driver Uninstall Installer
 Introduction Destination Select Installation Type Installation Summary 	You will be guided through the steps necessary to install this software.
	Go Back Continue





2-3 Press Close

